



**ASSURED ENERGY**  
Product Liability Insurance QBE



**30** YEAR LINEAR POWER WARRANTY  
ANNI GARANZIA LINEARE PRODUZIONE  
**20** YEAR PRODUCT WARRANTY  
ANNI GARANZIA PRODOTTO



**12V DC MODULES**  
FOR OFF-GRID SOLUTIONS



**SUITABLE FOR: SOLAR KITS,  
RVS, BOATS AND CABINS**



**MAXIMUM ADAPTABILITY**

**CELLS**



**TYPE:**  
POLY 3BB-4BB

**FRAME**



**BACKSHEET**



**ELECTRICAL CHARACTERISTICS (STC)\***

	<b>OS10P</b>	<b>OS20P</b>	<b>OS30P</b>	<b>OS50P</b>
Nominal Output (Pmax)	10 W	20 W	30 W	50 W
Voltage at Pmax (Vmp)	16.5 V	18.6 V	17.65 V	17.72 V
Current at Pmax (Imp)	0.61 A	1.08 A	1.70 A	2.83 A
Open Circuit Voltage (Voc)	20 V	22.14 V	21.17 V	21.26 V
Short Circuit Current (Isc)	0.67 A	1.16 A	1.90 A	3.17 A
Module Efficiency	9.84%	10.84%	10.59%	13.61%
Solar Cells	36 (4x9)	36 (4x9)	36 (2x18)	36 (4x9)
Cells Dimensions	52x36mm / 2x1.4"	78x52 mm / 3x2"	156x39 mm / 6x1.5"	156x52 mm / 6x2"
Cable	-	-	50 cm + MC4	50 cm + MC4
Dimensions	415x245x17 mm 16.3x9.6x0.67"	535x345x25 mm 21x13.5x1"	798x355x30 mm 31.4x13.9x1.2"	545x674x30 mm 21.5x26.5x1.2"
Weight	1.3 Kg / 2.86 lbs	2.2 Kg / 4.85 lbs	3.4 Kg / 7.49 lbs	4.2 Kg / 9.26 lbs

**ELECTRICAL CHARACTERISTICS (STC)\***

	<b>OS80P</b>	<b>OS100P</b>	<b>OS150P</b>
Nominal Output (Pmax)	80 W	100 W	150 W
Voltage at Pmax (Vmp)	17.78 V	17.80 V	17.64 V
Current at Pmax (Imp)	4.50 A	5.62 A	8.51 A
Open Circuit Voltage (Voc)	21.33 V	21.36 V	21.17 V
Short Circuit Current (Isc)	5.03 A	6.26 A	9.51 A
Module Efficiency	12.76%	14.40%	15.04%
Solar Cells	36 (4x9)	36 (4x9)	36 (4x9)
Cells Dimensions	156x93 mm / 6x3.6"	156x104 mm / 6x4"	156x156 mm / 6x6"
Cable	50 cm + MC4	50 cm + MC4	50 cm + MC4
Dimensions	930x674x35 mm 36.6x26.5x1.4"	1030x674x35 mm 40.5x26.5x1.4"	1480x674x35 mm 58.3x26.5x1.4"
Weight	7.15 Kg / 15.76 lbs	8 Kg / 17.64 lbs	9.9 Kg / 21.82 lbs

\*STC: (Standard Test Condition): Irradiance 1000W/m<sup>2</sup>, Module Temperature 25°C, Air Mass 1.5

It is important to point out, that all technical specifications, information and figures contained in this datasheet are estimated values. Peimar reserves the right to change the technical specifications, information and figures contained in this document at any time without notice. SA\_06/2019